



# AUTOMATIC DUAL SIDED PRESSURE SENSITIVE LABELING MACHINE

with Tamp Rollers and Wrap Station

## Key Features

- Dual Label Heads Can Displace 8" Tall Labels
- Touch Screen Control System
- Built for 3 shift operations
- Sanitary Stainless Steel Frame
- Easy Adjusting Hand Wheels for Quick Setup
- Variable Speed Infeed Separator Wheel
- Two Labeling Heads (Front & Back labeling)
- 3 Roller System (Registration & Long Labels)
- Servo Synchronized Stabilizing Top Belt
- Tamp Rollers
- Synchronized Operation for Easy On the Fly Adjustments

## Touch Screen Controls

- Turns Conveyor On/Off
- 8 Speed Selections
- Fully Synchronized Conveyor with 8 Different Speed Selections
- Auto Teach for new labels
- On-Screen trouble shooting & Help Menus
- Missing Label Detector
- Label Count Down (for precise run of set number of labels) to Auto-Shut Off
- Simple straight forward Operator Controls.

## Optional Features

- Hot Stamp Date/Lot Coder
- Label Head & Top Hold Down Belt Motor Package,
- Alpha Numeric Starter Kit
- Bottle Separator Assembly
- Wheel Orientation For Ovals
- Clear Label Sensor
- Cantering Label Heads for Conical Bottles



Optional: Hot Stamp Coder



# SAPS-218



# AUTOMATIC DUAL SIDED PRESSURE SENSITIVE LABELING MACHINE

with Servo Synchronized Stabilizing Top Belt and Wrap Station



Sharp's **APS-218** is economical, efficient, easy to operate and can dispense up to a 8" (20.3 cm) tall labels. This automatic labeling system comes equipped with a 6" (15.25 cm) wide 10 ft. (304 cm) variable speed conveyor. Additional features include, a stepper motor drive for label, power assisted web take up, front back tamp station, top hold down belt, auto speed adjust (all motors synchronized), and Photo Eye (non contact) sensors for label gaps and containers. The easy to use touch screen programming makes it simple to change bottle and label sizes on the fly. Its two labeling heads allow for single or front and back labeling of containers.

The speed, versatility, and reliability of the **APS-218** is unmatched compared to the other industry leaders in labeling equipment technology, and offered at a fraction of the price. Labelette Labelers are ideal for all plastic, metal, fiber, and glass containers. The **APS-218** handles cylindrical as well as square and oblong containers.

## Specifications

### Dimensions:

Height: 54" (137.16 cm)

Length: 120" (304.8 cm)

Depth: 60" (152.4 cm)

### Weight:

Approx. 527 lbs. (239.04 kg)

### Labeling Speed:

Up to 200 CPM

### Label Size:

Length: 0.75"-18" (1.9-45.7 cm)

Height: 0.75" - 8" (1.9-20.3 cm)

### Electrical:

110 VAC, 10 AMPS

(220 VAC option available)

### Feature Comparison Chart

	Sharp	Competitors
• All motors are automatically synchronized for consistent efficient labeling .....	<b>YES</b>	<b>NO</b>
• No repositioning of label sensor is required for various label lengths .....	<b>YES</b>	<b>NO</b>
• One touch HMI Touch screen adjustment to change labeling speed .....	<b>YES</b>	<b>NO</b>
• Up to 30 job memories .....	<b>YES</b>	<b>NO</b>
• Touch screen with help menu's and trouble shooting guide .....	<b>YES</b>	<b>NO</b>
• Total bottles labeled counter .....	<b>YES</b>	<b>NO</b>

